




ICC# ESR-3815

Carbon Fiber/Kevlar
ReGrid Technology with Adhesive
Riveting for concrete crack repair and
structural reinforcement

Product Description: The Crack Stitch by Fortress is a pre-impregnated, bi-directional carbon fiber / Kevlar® open grid near surface mount reinforcement crack repair product for the strengthening of concrete and masonry structures. Crack Stitches are filled installed utilizing Fortress Xtreme 4070 resin to form a Carbon Fiber Reinforced Polymer (CFRP) system.



PRODUCT USE

Key Features:

- Non Corrosive
- Ultra High Strength, pre-cured carbon
- Open Grid allows for mechanical bonding through adhesive riveting technology

Target Applications

- Slab floor crack repair and control
- Masonry wall crack repair and control
- Poured concrete crack repair and control
- Swimming pool crack repair and control
- Parking surface crack repair and control
- Reinforcement of concrete with compromised reinforcement steel (ReBar)



PRODUCT SPECIFICATIONS

Base Material Carbon Filament tows woven into a grid

Shelf Life Unlimited

Color Black (Carbon) / Yellow (Aramid)

Carbon Filament Tensile Strength, ksi (MPa) 800 (5,515)

Carbon Filament Tensile Modulus, ksi (MPa) 36,000 (248,000)

Fortress Crack Stitch Nominal Size in (mm) 10.0 x 7/8 x 0.090 (254 x 22.2x 2.3)

Laminated CFRP System Mechanical Physical Properties

	Ultimate Tensile Strength ¹ f_{tu} Ksi (MPa)	Modulus of Elasticity ¹ E_f Ksi (GPa)	Ultimate Strain at Rupture ϵ^*_{fu} in/in (mm/mm)
Typical (mean) Values (μ)	342.4 (2361)	21,616 (149)	1.59%
Std. Dev (σ)	13.9 (96)	750 (5.2)	
min tested	325.7 (2246)	20,326 (140.1)	
ACI Design ($\mu-3\sigma$)	300.7 (2073)	19,334 (133.3)	

Laminate results at room temperature using SKRS Room 77°F curing epoxy resin

¹ASTM D3039 ²Thickness of cured laminate = 0.909 in (2.3mm)

HOW TO USE

Packaging: Standard packaging includes cardboard boxes. Labeled on box.

Preparation. Protect the work area from standing water and inclement weather. Surfaces may be damp. Surfaces must be clean and sound. Spalling or other damaged concrete must be removed to solid material. Make a straight saw cut perpendicular to the direction of lateral crack expansion, no less than 1/8" (3.175mm) wide and 3/4" (19.05mm) deep. Dry fit stitch to insure proper cut width and depth. Use oil free compressed air or vacuum to remove concrete dust. Add Xtreme 4070 epoxy to saw cut and place crack stitch into saw cut. Keep Crack Stitches free from contamination. Store in a clean and dry area away from direct sunlight. Keep in original packaging until installation and protect from physical damage. Remove dust, dirt, and any other foreign materials.

Cutting. Fortress Crack Stitches™ may be cut to desired length with sharp snips

Epoxy Resin. Fortress Xtreme 4070 epoxy resin is recommended for all applications for bonding Fortress Crack Stitches.

Applications. Fortress Crack Stitches can be used with various modulus resins. Either pourable or injection resin will interlock Fortress Crack Stitches.

Qualifications. Except for standard Fortress installations by Fortress qualified installers, each structural and life safety application requires the design and certification of a licensed professional engineer.

Cautions. A near surface mount applied CFRP system is a vapor barrier. Consult a licensed, professional engineer to evaluate results of encapsulating porous substrates. Installation should be performed only by a Fortress' trained and approved installer. Caution must be used when handling Fortress Crack Stitches. Gloves should be worn to protect against carbon dust skin irritation and exposed fiber ends. Use of an appropriate, properly fitted NIOSH approved respirator is recommended. As with any cutting and adhesive operations proper eye protection should be used. Always follow OSHA and site safety requirements.

Keep out of reach of Children - Keep container tightly closed - not for internal consumption - For industrial use only.

The information contained herein is included for illustrative purposes only and is, to the best of our knowledge, accurate and reliable. Fortress cannot however, under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As Fortress has no control over use to which others may put its product, the products are to be tested to determine if suitable for a specific application and to verify if our information is valid for a particular application. Responsibility remains with the specifier, contractor, installer, user, and owner of the design, application and proper installation of each product. Fortress receives the right to change the properties of its products without notice. **Prior to each use of any Fortress product, the user must always read, understand, and follow the warning and instruction on the product's most current Technical Product Data sheet, product label, and Material Safety Data Sheet available at www.FortressStabilization.com**

LIMITED WARRANTY, DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: Fortress Stabilization Systems ("Seller") warrants its products to be free of defects in the material and workmanship for a period of ONE (1) YEAR from the date of purchase. Under this Warranty and limitation of liability, Fortress will provide, at no charge, product and containers to replace any product. Fortress' obligation hereunder, is limited solely to such replacement and is subject to receipt by Fortress of a written notice of any alleged defects, promptly after discovery thereof, within the warranty period. Absence of such notice in writing during the warranty period constitutes a waiver of all claims with respect to such product. This Warranty excludes discoloration or change in visual appearance of the product due to the accumulation of or streaking of dirt or other airborne material deposited on the surface from the atmosphere. Fortress does no warranty the color-fastness of any product unless specifically stated otherwise. Before application, the Buyer shall determine the suitability of the product for the intended use and Buyer assumes all risks and liabilities whatsoever in the connection therewith. THIS WARRANTY IS MADE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HERBY DISCLAIMED. IT IS UNDERSTOOD AND AGREED THAT BUYER'S SOLE REMEDY, AND THEREFORE SELLER'S LIABILITY, WHETHER IN CONTRACT, TORT, WARRANTY IN NEGLIGENCE, OR OTHERWISE, SHALL BE LIMITED TO THE RETURN OF THE PURCHASE PRICE PAID BY PURCHASE OR REPLACEMENT OF ANY DEFECTIVE GOODS SOLD BY SELLER AND UNDER NO CIRCUMSTANCES SHALL SELLER BE LIABLE FOR SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES. THE PRICE STATED FOR THE GOODS IS A CONSIDERATION IN LIMITING SELLER'S LIABILITY. The terms of this paragraph may not be orally modified. THERE ARE NO WARRANTIES, WHICH EXTEND BEYOND THE FACE HEREOF.



(800) 207-6205 www.FortressStabilization.com 184 w. 64th St. Holland, MI 49423 USA